





N°	REF	DESCRIPTION	DESCRIPTION	SPEC	QTT
1	HOTSAUCE1_1	RUBBER FEET	PIEDS EN CAOUTCHOUC	φ25*φ21*18mm/Noir/φ4.2	4
2	HOTSAUCE1_2	BOTTOM PLATE	PLAQUE INFERIEURE	BM4S-04	1
3	HOTSAUCE1_3	PRESS PLATE	PLAQUE DE PRESSION	BM4S-05	1
4	HOTSAUCE1_4	HEATER	RESISTANCE CHAUFFANTE	200W/230V/BM4D-01	1
5	HOTSAUCE1_5	HOUSING	CARTER	BM4S.01	1
6	HOTSAUCE1_6	CERAMIC TERMINAL BLOCK	BORNIER CERAMIQUE	30A/XL-805/	1
7	HOTSAUCE1_7	POWER LINE	CORDON D'ALIMENTATION	H05RN-F/3*1.0mm ² 1.6L/KH-9902	1
8	HOTSAUCE1_8	STRAIN RELIEF	PASSE-CABLE DE DECHARGE DE TRACTION	10mm	1
9	HOTSAUCE1_9	1/6 GN PAN	BAC GN 1/6	INOX304	1
10	HOTSAUCE1_10	DOWEL PIN	GOUPILLE DE POSITIONNEMENT	304/Ø6*12 (M5*6)	4
11	HOTSAUCE1_11	NUT	ECROU	304/metal M5/H-10.5	4
12	HOTSAUCE1_12	LID	COUVERCLE	BM4S.02.01-01	1
13	HOTSAUCE1_13	LID HANDLES	POIGNEES DE COUVERCLE	M6*12	1
14	HOTSAUCE1_14	SOUP SPOON	LOUCHE	INOX	1
15	HOTSAUCE1_15	SWITCH	INTERRUPTEUR	KCD2/16A 250V T105	1
16	HOTSAUCE1_16	HEAT INDICATOR LIGHT	VOYANT DE CHAUFFE	φ14	1
17	HOTSAUCE1_17	85 DEGREE THERMOSTAT	THERMOSTAT 85 °C	WYE-085-A5/85°C	1
18	HOTSAUCE1_18	KNOB	BOUTON DE COMMANDE	A5/20B-21	1
19	HOTSAUCE1_19	THERMAL CUT OUT	THERMOSTAT DE SECURITE 125°C	KSD301/250V/15A/125°C/	1