





N°	REF	DESCRIPTION	DESCRIPTION	SPEC	QTT
1	HOTSAUCE1_1	RUBBER FEET	PIEDS EN CAOUTCHOUC	φ25*φ21*18mm/Noir/φ4.2	4
2	HOTSAUCE2_2	BOTTOM PLATE	PLAQUE INFERIEURE	BM4D-04	1
3	HOTSAUCE2_3	PRESS PLATE	PLAQUE DE PRESSION	BM4D-05	2
4	HOTSAUCE2_4	HEATER	RESISTANCE CHAUFFANTE	200W/230V/BM4D-01	2
5	HOTSAUCE2_5	HOUSING	CARTER	BM4D.01	1
6	HOTSAUCE1_6	CERAMIC TERMINAL BLOCK	BORNIER CERAMIQUE	30A/XL-805	1
7	HOTSAUCE1_7	POWER LINE	CORDON D'ALIMENTATION	H05RN-F/3*1.0mm <sup>2</sup> 1.6L/KH-9902	1
8	HOTSAUCE1_8	STRAIN RELIEF	PASSE-CABLE DE DECHARGE DE TRACTION	10mm	1
9	HOTSAUCE2_9	1/6 GN PAN	BAC GN 1/6	200 depth / 1/6 GN /INOX304	2
10	HOTSAUCE1_10	DOWEL PIN	GOUPILLE DE POSITIONNEMENT	304/Ø6*12 (M5*6)	4
11	HOTSAUCE1_11	NUT	ECROU	304/metal M5/H10.5	4
12	HOTSAUCE2_12	LID	COUVERCLE	BM4D.02.01-01	1
13	HOTSAUCE1_13	LID HANDLES	POIGNEES DE COUVERCLE	M6*12	1
14	HOTSAUCE2_14	SOUP SPOON	LOUCHE	INOX304	2
15	HOTSAUCE1_15	SWITCH	INTERRUPTEUR	KCD2/16A 250V T105	1
16	HOTSAUCE1_16	HEAT INDICATOR LIGHT	VOYANT DE CHAUFFE	φ14	2
17	HOTSAUCE1_17	85 DEGREE THERMOSTAT	THERMOSTAT 85 °C	WYE-085-A5/850 L/85°C	2
18	HOTSAUCE1_18	KNOB	BOUTON DE COMMANDE	A5/20B-21	2
19	HOTSAUCE1_19	THERMAL CUT OUT	THERMOSTAT DE SECURITE 125°C	KSD301/250V/15A/125°C	2