



### MODEL 1200

380-415 V 3 ~ N 50/60 Hz  
Max Watt 7200 W  
Max Amps 12.7 A

Three-Phase edition of MODEL 1200 with all optionals operations in function.

- |                                     |                                      |
|-------------------------------------|--------------------------------------|
| EMF : Electromagnetic Filter        | TFB : Thermofuse Boiler              |
| UI : Users Interface                | TFT : Thermofuse Tank                |
| MS : Magnetic Door Switch           | IV : Inlet Valve                     |
| PST : Pressure Switch               | HRV : Hot Rinse Valve                |
| PSBT : Pressure Switch (Break Tank) | CRV : Cold Rinse Valve               |
| TPB : Thermo Probe Boiler           | PPM : Pressure Pump Motor            |
| TPT : Thermo Probe Tank             | DPM : Draining Pump Motor *          |
| DTM : Detergent Pump Motor          | BHE : Boiler/Booster Heating Element |
| RAM : Rinse Aid Pump Motor          | THE : Tank Heating Element           |
| K1/K2/K3/K4 : Magnetic Contactors   | WPM : Washing Pump Motor             |
| K5 : Microrelay                     | C : Capacitor                        |
| OR : Overload Relay                 | * OPTIONAL                           |